



LRQ 0960929



Wrapped Metric Plain Bearings. Acetal X Type

Reference	I.D.	O.D.	Recommended Tolerances				Bearing Size when fitted		Oil hole	Standard Length Options					
			Housing		Shaft		Bore		Diameter	Tolerance +/- 0-25mm					
	(mm)	(mm)	(mm)						(mm)	(mm)					
TPX08 x L	8	10	0	+0.015	0	-0.022	8.040	8.107	no hole	8	10	12			
TPX10 x L	10	12	0	+0.018	0	-0.022	10.040	10.110	4	10	12	15	20		
TPX12 x L	12	14	0	+0.018	0	-0.027	12.040	12.110	4	10	12	15	20	25	
TPX14 x L	14	16	0	+0.018	0	-0.027	14.040	14.011	4	15	20	25			
TPX15 x L	15	17	0	+0.018	0	-0.027	15.040	15.108	4	10	12	15	25		
TPX16 x L	16	18	0	+0.018	0	-0.027	16.040	16.110	4	15	20	25			
TPX18 x L	18	20	0	+0.021	0	-0.027	18.040	18.111	4	15	20	25			
TPX20 x L	20	23	0	+0.021	0	-0.033	20.050	20.131	4	10	15	20	25	30	
TPX22 x L	22	25	0	+0.021	0	-0.033	22.050	22.131	6	15	20	25	30		
TPX24 x L	24	27	0	+0.021	0	-0.033	24.050	24.131	6	15	20	25	30		
TPX25 x L	25	28	0	+0.021	0	-0.033	25.050	25.131	6	15	20	25	30		
TPX28 x L	28	32	0	+0.025	0	-0.033	28.060	28.155	6	20	25	30			
TPX30 x L	30	34	0	+0.025	0	-0.033	30.060	30.155	6	20	30	40			
TPX32 x L	32	36	0	+0.025	0	-0.039	32.060	32.155	6	20	30	35	40		
TPX35 x L	35	39	0	+0.025	0	-0.039	35.060	35.155	6	20	30	35	50		
TPX40 x L	40	44	0	+0.025	0	-0.039	40.060	40.155	8	20	30	40	50		
TPX45 x L	45	50	0	+0.025	0	-0.039	45.080	45.195	8	20	30	40	45	50	
TPX50 x L	50	55	0	+0.030	0	-0.039	50.080	50.200	8	40	50	60			
TPX55 x L	55	60	0	+0.030	0	-0.046	55.080	55.200	8	20	25	30	40	50	60
TPX60 x L	60	65	0	+0.030	0	-0.046	60.080	60.200	8	30	40	60	70		
TPX65 x L	65	70	0	+0.030	0	-0.046	65.100	65.262	8	40	50	60	70		
TPX70 x L	70	75	0	+0.030	0	-0.046	70.100	70.262	8	25	40	50	65	70	80
TPX75 x L	75	80	0	+0.030	0	-0.046	75.100	75.262	9.5	40	60	80			
TPX80 x L	80	85	0	+0.035	0	-0.046	80.100	80.267	9.5	40	60	80	100		
TPX85 x L	85	90	0	+0.035	0	-0.054	85.100	85.267	9.5	30	40	60	80	100	
TPX90 x L	90	95	0	+0.035	0	-0.054	90.100	90.267	9.5	25	40	60	80	90	100
TPX95 x L	95	100	0	+0.035	0	-0.054	95.100	95.267	9.5	60	100				
TPX100 x L	100	105	0	+0.035	0	-0.054	100.100	100.267	9.5	50	60	80	95	115	
TPX105 x L	105	110	0	+0.035	0	-0.054	105.100	105.267	9.5	60	115				
TPX110 x L	110	115	0	+0.035	0	-0.054	110.100	110.267	9.5	60	110	115			
TPX115 x L	115	120	0	+0.035	0	-0.054	115.100	115.267	9.5	50	70				
TPX120 x L	120	125	0	+0.040	0	-0.054	120.100	120.272	9.5	60	100	110			
TPX125 x L	125	130	0	+0.040	0	-0.063	125.100	125.272	9.5	60	100	110			
TPX130 x L	130	135	0	+0.040	0	-0.063	130.130	130.280	no hole	50	60	80	100		
TPX135 x L	135	140	0	+0.040	0	-0.063	135.130	135.280	no hole	60	80				
TPX140 x L	140	145	0	+0.040	0	-0.063	140.130	140.280	no hole	50	60	80	100		
TPX145 x L	145	150	0	+0.040	0	-0.063	145.130	145.280	no hole	100					
TPX150 x L	150	155	0	+0.040	0	-0.063	150.130	150.280	no hole	50	60	80	100		
TPX160 x L	160	165	0	+0.040	0	-0.063	160.130	160.280	no hole	50	60	80	100		
TPX170 x L	170	175	0	+0.040	0	-0.063	170.130	170.280	no hole	50	60	80	100		
TPX180 x L	180	185	0	+0.046	0	-0.063	180.130	180.286	no hole	50	60	80	100		
TPX190 x L	190	195	0	+0.046	0	-0.072	190.130	190.286	no hole	50	60	80	100	120	
TPX200 x L	200	205	0	+0.046	0	-0.072	200.130	200.286	no hole	50	60	80	100	120	
TPX220 x L	220	225	0	+0.046	0	-0.072	220.130	220.286	no hole	50	60	80	100	120	
TPX240 x L	240	245	0	+0.046	0	-0.072	240.130	240.286	no hole	50	60	80	100	120	
TPX250 x L	250	255	0	+0.052	0	-0.072	250.130	250.292	no hole	50	60	80	100	120	
TPX260 x L	260	265	0	+0.052	0	-0.081	260.130	260.292	no hole	50	60	80	100	120	
TPX280 x L	280	285	0	+0.052	0	-0.081	280.130	280.292	no hole	50	60	80	100	120	
TPX300 x L	300	305	0	+0.052	0	-0.081	300.130	300.292	no hole	60	80	100	120		

Non-standard lengths can be supplied. If the size you require is not listed please contact our sales dept. We also offer a specialised machining service for low volume non-standard sizes and tolerances.

Bowman International Limited reserve the right to change specifications without prior notice E & OE